

3A



## Drive Chain Cleaning and Lubricating

- 1) Remove dirt and dust from the drive chain (1). Be careful not to damage the seal ring.
- 2) Clean the drive chain (1) with a sealed drive chain cleaner, or water and neutral detergent.

**NOTICE:**

**Cleaning the drive chain improperly can damage seal rings and ruin the drive chain.**

- **Do not use a volatile solvent such as paint thinner, kerosene and gasoline.**
- **Do not use high pressure cleaner to clean the drive chain.**
- **Do not use wire brush to clean the drive chain.**

- 3) Use a soft brush to clean the drive chain (1). Be careful not to damage the seal ring even through using a soft brush.
- 4) Wipe off water and neutral detergent.
- 5) Lubricate with a motorcycle sealed drive chain (1) lubricant or high viscosity oil.

**NOTICE:**

**Some drive chain lubricant contains solvents and additives which could damage the seal rings in the drive chain.**

**Use sealed drive chain lubricant which is specifically intended for use with sealed drive chains.**

- 6) Lubricate both front and back plates of the drive chain (1).
- 7) Wipe off excess lubricant after lubricating all around of the drive chain (1).

**NOTE:**

**The standard drive chain is a RK 525SMOZ8. SUZUKI recommends to use this standard drive chain as a replacement.**

