

3A



Drive Chain Cleaning and Lubricating

- 1) Remove dirt and dust from the drive chain (1). Be careful not to damage the seal ring.
- 2) Clean the drive chain (1) with a sealed drive chain cleaner, or water and neutral detergent.

NOTICE:

Cleaning the drive chain improperly can damage seal rings and ruin the drive chain.

- **Do not use a volatile solvent such as paint thinner, kerosene and gasoline.**
- **Do not use high pressure cleaner to clean the drive chain.**
- **Do not use wire brush to clean the drive chain.**

- 3) Use a soft brush to clean the drive chain (1). Be careful not to damage the seal ring even through using a soft brush.
- 4) Wipe off water and neutral detergent.
- 5) Lubricate with a motorcycle sealed drive chain (1) lubricant or high viscosity oil.

NOTICE:

Some drive chain lubricant contains solvents and additives which could damage the seal rings in the drive chain.

Use sealed drive chain lubricant which is specifically intended for use with sealed drive chains.

- 6) Lubricate both front and back plates of the drive chain (1).
- 7) Wipe off excess lubricant after lubricating all around of the drive chain (1).

NOTE:

The standard drive chain is a RK 525SMOZ8. SUZUKI recommends to use this standard drive chain as a replacement.

